



5 YEARS WARRANTY ☆

- AC Charging
- Available in 230V or 110V



Typical uses:



- 230V or 110V models available
- RCBO protection
- Ultra-rugged case with Lifetime Warranty
- Pure Sinewave output
- 3000+ Cycles Life Expectancy
- LCD Display Controller
- Fan assisted cooling
- IP67 Waterproof case

TECHNICAL SPECIFICATIONS		GenZero 3000W	GenZero 1500W	GenZero 600W
	Continuous Output	3000W	1500W	600W
	Peak Output	6000W	3000W	1200W
	Battery Capacity (Wh)	1540Wh	922Wh	615Wh
	Battery Type	LiFePO4		
	Charging Time	4 Hours	2 Hours	3 Hours
	Ingress Protection	IP67		
	Storage/Operating Temperature	-10 TO 45 °C		
	Charge Methods	AC mains (Supplied) • Solar panel charger or Vehicle charger (Optional)		
	AC Output Voltage	Select: 110V or 230V		
	USB Outputs	1 x USB + 1 x USB-C		
	Life Of Battery	3000+ cycles		
	AC Charger Supplied	10A	10A	5A
	NET Weight	31.8kg	18.2kg	12.5kg
	Dimensions	579 x 465 x 297mm	505 x 409 x 257mm	429 x 328 mm x 236mm
	Product Code	GENZERO-3000W	GENZERO-1500W	GENZERO-600W



Optional Expandable Battery Packs

- Add more power 1540Wh each
- 4 Hours charging time



- Up to 8 Additional, Capacity 13860 (Wh)
- Battery Type: LiFePO4
- Weight: 18kg each
- Dimensions: L429 x W328 x H236mm
- 3000+ Cycles Life Expectancy

Distributed by: