

CTRS - ELS00000 SERIES - Compact card Dispenser





MAIN FEATURES

- · Side frame supporting cartridge
- · Removable cartridge
- · Stepping motor and photosensors ticket positioning
- Contactless Card management based on Mifare Standard ISO/IEC 14443 A/B + ISO15693
- · Easy card loading and mainaenance
- · Microprocessor based electronics
- SMD low consumption electronic circuits
- Communication by means of RS232/RS485, USB or ethernet

TECHNICAL SPECIFICATIONS

OVERALL DESCRIPTION

Outline dimensions
 Cartridge
 Weight
 320(H) x 165(L) x 155(W) mm
 240(H) 300 cards x0.80 mm
 3.0 Kg (Approximately)

•Electronics : Specific PCB

•Stacker capacity : 150/300/500/600/1000 pcs

•Ticket motion : Stepping motor•Transport method : Rollers and sled•Ticket Sensors : Photosensors

•Output interface : RS232 / RS485 / ethernet / USB

·Power requirements : +24V DC +/-10% 3A

CARD/TICKET SPECIFICATIONS

•**Length** : 85.60 mm •**Width** : 53.98 mm

·Thickness : From 0.30 to 1.00 mm

ENVIRONMENTAL

•Operating temperature : From 0 to +55°C
•Storage temperature : From -20 to +60°C
•Relative humidity : From 20 to 80%
(No condensation)

