

ROAD MARKING MATERIALS



EXTREMELY HEAVY TRAFFIC / ACRYLIC COLD PLASTICS

SOLID CONTENT: 100%, THICKNESS UP TO 7 mm, FAST CURING

ACRYLIC COLD PLASTICS	SYSTEM			APPLICATION						
	DENSITY	100:1	98:2	MANUAL	EXTRUDOR	AGGLOMERATES	DOTED	TAKTILE	ANTISKID	FILM THICKNESS
SIGNODUR struktural	1,85	•	•	•	•	•	•	•		2 mm
SIGNODUR G	1,85	•	•	•	•			•		2 mm
SIGNODUR G reibeplast	1,85	•	•	•	•				•	up to 7 mm

VERY HEAVY TRAFFIC / ACRYLIC COLD SPRAY PLASTICS AND POLIURETANS

SOLID CONTENT: 100% KSP; 75% PUR, THICKNESS UP TO 1 mm, VERY FAST CURING

ACRYLIC COLD SPRAY PLASTICS AND POLIURETANS	DENSITY	SYSTEM			APPLICATION	WET FILM THICKNESS
		98:2	1:1	DIFFERENT RATIOS		
SIGNODUR KSP	1,55	•	•		Spraying	0,4 - 1 mm
SIGNOCRYL traffic 2K PUR	1,55			•	Spraying	0,5 mm

HEAVY TRAFFIC / ACRYLIC MARKING PAINTS

SOLID CONTENT: ≥ 75%, THICKNESS UP TO 0,6 mm, FAST DRYING

ACRYLIC MARKING PAINTS	DENSITY	SOLVENT			APPLICATION		WET FILM THICKNESS
		NON - AROMATIC	AROMATIC	WATER	AIRLESS	AIR SPRAY	
VERONIL A	1,60	•			•		0,4 - 0,6 mm
SIGNOCRYL (E)	1,58	•	•		•	•	0,4 - 0,6 mm
HELIOCRYL (HS)	1,60	•	•		•	•	0,4 - 0,6 mm
HELIOCRYL AQ	1,63			•	•	•	0,4 - 0,6 mm

(E, HS) environmentally friendly

MODERATELY HEAVY TRAFFIC / ACRYLIC MARKING PAINTS

SOLID CONTENT: ≥ 75%, THICKNESS UP TO 0,6 mm, FAST DRYING

ACRYLIC MARKING PAINTS	DENSITY	SOLVENT		APPLICATION		WET FILM THICKNESS
		NON - AROMATIC	AROMATIC	AIRLESS	AIR SPRAY	
HELIOCRYL (E) Basic	1,55	•	•	•	•	0,4 - 0,6 mm
SIGNOCRYL (E) Basic	1,55	•	•	•	•	0,4 - 0,6 mm

(E) environmentally friendly

SPECIAL SOLUTIONS / MARKING PAINTS & ACRYLIC COLD PLASTICS

SPECIAL SOLUTIONS	MARKING PAINTS	ACRYLIC COLD PLASTICS
BICYCLE PATHS and other decorative or anti-skid solutions	SIGNOCRYL Cycle Paths	SIGNODUR (Struktural, G, G Reibeplast, Roll) SIGNODUR Transparent with aggregate
SPEED REDUCTION WARNINGS		SIGNODUR G Reibeplast
INDOOR MARKING on concrete	SIGNOCRYL 2K PUR	