

# OSC 5000

## Oil Spillage Removing Vehicle



The **OSC 5000** is built on a LADOG chassis 1250 (German production) and is ideal for cleaning larger surfaces and oil spills and other kind of contamination – e.g. chewing gum.

Our system is used to clean raceways, footways, roads and parking areas.  
The system is small, flexible und nearly everywhere applicable.

### Technical data:

Engine	EURO 3, 70 kW / EURO 6, 84 kW
Max. speed	60 km/h
Gross vehicle weight	5400 kg
Vehicle height	2000 mm
Wheel base	2600 mm
Tyres	245/75R16 AT

Material of superstructure	stainless steel 1.4301
Sludgetank	1500 Liter
Fresh water tank:	1000 Liter
Opening of tank door	hydraulically

### High performance, radial ventilator

- |                  |            |
|------------------|------------|
| - Driving power  | max. 19 kW |
| - Suction hose Ø | DN 170     |

### High pressure plunger pump

- |          |              |    |              |
|----------|--------------|----|--------------|
| - Q max. | 38 l/min     | OR | 31 l/min     |
| - P max. | max. 250 bar | OR | max. 300 bar |
| - Power  | 18,1 kW      |    | 18,1 kW      |
| - Drive  |              |    | hydraulic    |

### Surface Cleaner - Turbocleaner 1500

- |   |         |
|---|---------|
| - Hydraulic swiveling right & left approx.                  | 800 mm  |
| - Working width   | 1200 mm |
| - Special guide rollers, Ø 180 mm for easy passing of edges |         |

### Hotwater-therme

- |                      |                                |
|----------------------|--------------------------------|
| - Power              | 90 kW with flame monitoring    |
| - Operating pressure | up to 300 bar                  |
| - Energy             | diesel OR heating oil, 12 V DC |

