## **BLINDO 140**

REMOVABLE BOLLARDS BLINDO HAVE AN ARCHITECTURAL APPEARANCE SIMILAR TO THAT OF THE CSA OR PALMO SERIES, THIS ALLOWS A COMBINED USE OF ALL VERSIONS SIMULTANEOUSLY. THESE BOLLARDS ARE THE RESULT OF THE CONTINUOUS DEVELOPMENT OF MORE THAN 25 YEARS OF EXPERIENCE.

- MANUAL MOTION, THE MOST RECOMMENDED SOLUTION TO BE USED TO CONTROL THE TRANSIT OR THE STATIONING OF VEHICLES IN DAILY TRAFFIC LIMITED ZONES.
- $\circ$  THE INSTALLATION IS MADE FIXING THE BOLLARD ON THE DEDICATED BURRIED FORMWORK.
- HOT GALVANIZED PIPE, FOR A LONG TERM RESISTANCE TO WEAR.
- WIDE RANGE OF CUSTOMIZATION: CUSTOM COLOURS ETC. (SEE ACCESSORIES AND OPTIONAL ITEMS SHEET)



Technical Data

TYPE OF BOLLARD	Cod.	BLINDO140/12	BLINDO140/4	BLINDO140/4 I
HEIGHT OF CYLINDER	mm	500 / 700	500 / 700	500 / 700
THICKNESS OF FIXED CYLINDER	mm	12,5	4	4
DIAMETER OF FIXED CYLINDER	mm	140	140	140
TYPE MATERIAL OF CYLINDER		FE 510	FE 360	INOX304
FINISHING OF CYLINDER		POLYEST	SATIN	
TREATMENT OF CYLINDER		HOT GAL		
REFLECTIVE ADHESIVE STRIPE		•	•	<b>8</b> •
RESISTANCE TO BREAKING	J	79.000	39.000	79.000
RESISTANCE TO DEFORMATION (JOULE)	J	4.000	2.000	3.000
TOTAL WEIGHT OF BOLLARD H500 (ALUMINIUM HEAD)	Kg	26	8	13
TOTAL WEIGHT OF BOLLARD H700 (ALUMINIUM HEAD)	Kg	35	10	15

BLINDO 140 H500 Cod. 0342601 0341601 0341701

REMOVABLE BOLLARD FIXED ON THE GROUND THROUGH BURIED FORMWORK, ALUMINIUM HEAD

BLINDO 140 H700 Cod. 0342611 0341611 0341711

REMOVABLE BOLLARD FIXED ON THE GROUND THROUGH BURIED FORMWORK, ALUMINIUM HEAD





