## TRAFFIC PLATE

TRAFFIC PLATE TYRE KILLER WITH HYDRAULIC MOTION, IS COMPOSED BY IRON SPURS WITH 10MM OF THICKNESS. IN ORDER TO IMPROVE ITS EFFICENCY, IT CAN BE INSTALLED AND USED IN COUPLE WITH OTHER MAC'S DEVICES.

- HYDRAULIC MOTION.
- THE PRODUCTS IS HOT GALVANIZED IN ORDER TO IMPROVE ITS RESISTANCE TO THE WEAR.
- WIDE RANGE OF CUSTOMIZATION: CUSTOM COLOURS (SEE ACCESSORIES AND OPTIONAL ITEMS SHEET).

|                               |                       | <b>)</b> | ĝ | ĝ  | Ĵ  | Î | Î | Î | Î | - | Ê | Î | ĝ | ĝ | Î  | Î | ĝ | Ĵ |  | - |
|-------------------------------|-----------------------|----------|---|----|----|---|---|---|---|---|---|---|---|---|----|---|---|---|--|---|
| Fin                           |                       | 335      |   | 10 | 00 | 4 |   |   | 4 | 1 |   | 4 | v |   | r. | 1 | 4 |   |  | 4 |
| 100<br>80<br>90<br>284<br>620 | 154 2002<br>Lunghezza |          |   |    |    |   |   |   |   |   | - |   |   |   |    |   |   |   |  |   |

| TRAFFIC PLATE  | Cod. | TRAFFIC PLATE  |  |
|--|------|----------------|--|
| MATERIAL OF THE SPURS                                |      | INOX           |  |
| FINISHING OF THE SPURS                               |      | INOX           |  |
| FORMWORK AND STRUCTURE TREATMENT                     |      |                |  |
| COVER FINISHING                                      |      | HOT GALVANIZED |  |
| THICKNESS  | mm   | 10             |  |
| LOAD CHARGE RESISTANCE                               | KG   | 40.000         |  |
| SECURITY PRESSURE SWITCH                             |      | -              |  |
| DAILY CYCLES INTENSIVE USE (1 CYCLE EVERY 3 SECONDS) |      | 2.400          |  |
| CYCLES WITHOUT MAINTENANCE BEFORE BREAKING           |      | 1.500.000      |  |
| MAX WORKING PRESSURE                                 | BAR  | 30             |  |
| PUMP PROTECTION DEGREE                               | IP   | 67             |  |
| POWER CONSUMPTION                                    | W    | 500            |  |
| POWER SUPPLY   | Vac  | 230V / 50Hz    |  |
| WORKING TEMPERATURE                                  | °C   | -20 / +80      |  |
| ROSH PRODUCT   |      | •              |  |
| • = standard   |      |                |  |
| r = non standard                                     |      |                |  |

| HYDRAULIC UNDERGROUNDED TYRE KILLER h100 pitch 100 | Length | Cod.      |  |
|--|--------|-----------|--|
|  | 2000   | 039510532 |  |
|  | 3000   | 039510533 |  |
|  | 4000   | 039510534 |  |
|  | 5000   | 039510535 |  |
|  | 6000   | 039510536 |  |
| non-standard cost every 250mm                      |        | 039510530 |  |
| manual pump  |        | 035106000 |  |

170



ANTENNA 433 Mhz STAINLESS STEEL WITH CABLE 7m



TWO COILS MAGNET. INDUCTOR FOR LOOPS OF METAL REVEAL.



24Volt DC/AC

1650042







info@mac-srl.it

1630079

1

)ptional

MAC S.r.l. - Via Enrico Mattei n°9 - Loc. MORCIOLA - 61022 VALLEFOGLIA (PU) - Tel.: +39 0721 495447 - Fax: +39 0721 495438 Cod. Fisc. - P. Iva n°02246440412 - Iscr. Reg. Imprese di Pesaro Urbino n°02246440412 - Cap. Soc. €60.000,00 i.v.

**@**